



Product Service

CERTIFICATE

No. Z2 115229 0001 Rev. 00

Holder of Certificate: **Belinus Solar B.V.**
Kapeldreef 60
3001 Leuven
BELGIUM

Certification Mark:



Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 701262117701-00

Valid until: 2026-07-04

Date, 2021-12-16



Product Service

CERTIFICATE

No. Z2 115229 0001 Rev. 00

Model(s):

BE72-166-GG-xxx, BE72-166-GG-F-xxx (xxx=430-470, in step of 5);
BE60-166-GG-xxx, BE60-166-GG-F-xxx (xxx=360-390, in step of 5);
BE48-166-GG-xxx, BE48-166-GG-F-xxx (xxx=290-310, in step of 5);
BE44-166-GG-xxx, BE44-166-GG-F-xxx (xxx=265-285, in step of 5);
BE40-166-GG-xxx, BE40-166-GG-F-xxx (xxx=240-260, in step of 5);
BE36-166-GG-xxx, BE36-166-GG-F-xxx (xxx=215-230, in step of 5);
BE32-166-GG-xxx, BE32-166-GG-F-xxx (xxx=195-205, in step of 5);

BE78-18X-GG-xxx, BE78-18X-GG-F-xxx (xxx=570-610, in step of 5);
BE72-18X-GG-xxx, BE72-18X-GG-F-xxx (xxx=530-560, in step of 5);
BE66-18X-GG-xxx, BE66-18X-GG-F-xxx (xxx=485-515, in step of 5);
BE60-18X-GG-xxx, BE60-18X-GG-F-xxx (xxx=440-465, in step of 5);
BE54-18X-GG-xxx, BE54-18X-GG-F-xxx (xxx=395-420, in step of 5);
BE48-18X-GG-xxx, BE48-18X-GG-F-xxx (xxx=350-375, in step of 5);
BE40-18X-GG-xxx, BE40-18X-GG-F-xxx (xxx=295-310, in step of 5);
BE36-18X-GG-xxx, BE36-18X-GG-F-xxx (xxx=265-280, in step of 5);
BE32-18X-GG-xxx, BE32-18X-GG-F-xxx (xxx=235-250, in step of 5).
xxx is standing for rated output power at STC.

Parameters:

Safety Class:	Class II
Max. System Voltage:	1500V DC
Construction:	Framed and frameless, with Junction box, cable and connector.
Fire Safety Class:	Class A according to UL790

Tested according to:

IEC 61215-1:2016
EN 61215-1:2016
IEC 61215-1-1:2016
EN 61215-1-1:2016
IEC 61215-2:2016
EN 61215-2:2017
IEC 61730-1:2016
EN IEC 61730-1:2018
EN IEC 61730-1:2018/AC:2018-06
IEC 61730-2:2016
EN IEC 61730-2:2018
EN IEC 61730-2:2018/AC:2018-06